

High Power Connector	Product type	JPC Part Number	NO. of contacts	Connector type	Material	Rated Current	Rated Voltage	Backshell (Straight/Right Angle)	Alignment Key	HVIL Function	IP Rating	Operating temperature range
	23A Series	XLP602	2 Port	Plug / Receptacle	Plastic	23A	900V DC	Straight	Code: A/B/C/D/E/F	Optional	IP67	-40~125℃
	32A Series	XL203/XL403	3 Port	Plug / Receptacle	Metal	32A	630V DC	Straight	-	XL203: No XL403: Yes	IP67	-40~125℃
	45A Series	XL60	2 Port	Plug / Receptacle	Metal	45A	1000V DC	Straight	Code: X/Y/U/Z	Optional	IP67	-40~125℃
		XLP603	3 Port	Plug / Receptacle	Plastic	45A	900V DC	Straight	Code: A/B/C/D/E	Optional	IP67	-40~125℃
	200A	TL200	1 Port	Plug / Receptacle	Metal	200A	1000V DC	Right Angle	Code: X/Y/U/V/W/T	Optional	IP67	-40~125℃
		PSL200	1 Port	Plug / Receptacle	Plastic	200A	1500V DC	Right Angle	-	Optional	-	-40~125℃
		XLP200	2 Port		Plastic	200A	1000V DC	Straight	Code: A/B/C	Optional	IP67	-40~125℃
	250A	TL300	1 Port	Plug / Receptacle	Metal	250A	1000V DC	Right Angle	Code: X/Y/U/V/W/T	Optional	IP67	-40~125℃
	Mini MSD	Mini MSD	-	Plug / Receptacle: Front / Rear Mount	Plastic	100/250/315/400A	750V DC	Straight	--	Optional	IP67, IP69K	-40~125℃